



## Material Safety Data Sheet

Comment [Bit1]: Seite: 1  
SDB

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product information

Trade name : Jet-Ag  
Use of the Substance / Preparation : Peroxyacetic acid-based sanitizer/disinfectant  
Function : Liquid horticulture, algaecide and fungicide (see label)  
Company : JET Harvest Solutions  
P.O. Box 915139  
Longwood, Florida 32791  
USA  
Telephone : 877-866-5773  
Fax : 407-298-2377  
U.S. EMERGENCY NUMBER : 407-619-3421  
Product Regulatory Services : 407-523-7842

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### Chemical nature

Preparation of peracetic acid, hydrogen peroxide, acetic acid and water in balance.

#### Information on ingredients / Hazardous components

Peracetic acid				
CAS-No.	79-21-0	Percent (Wt./ Wt.)		5 %
Hydrogen peroxide				
CAS-No.	7722-84-1	Percent (Wt./ Wt.)		20 < 30 %
Acetic acid				
CAS-No.	64-19-7	Percent (Wt./ Wt.)		6 < 10 %

#### Other information

This material is classified as hazardous under OSHA regulations.

### 3. HAZARDS IDENTIFICATION

#### \*\*\* EMERGENCY OVERVIEW \*\*\*

**Form**-liquid **Color**-colourless, clear **Odor**-stinging

Causes burns.

May cause fire.

Risk of decomposition in contact with incompatible substances, impurities, metals, alkalis, reducing agents.

Danger of decomposition if exposed to heat

see also section 10.

#### Eye contact

Corrosive, Causes eye burns.

#### Skin Contact

Corrosive, Liquid or vapor causes burns which may be delayed.

**Inhalation**

Possible discomfort: irritation of mucous lining (nose, throat, eyes), coughing.

**Ingestion**

Causes digestive tract burns.

---

**4. FIRST AID MEASURES****General advice**

Move out of dangerous area.  
Take care of your own personal safety.  
see section 8.

**Inhalation**

Take affected persons out into the fresh air.  
Possible discomfort: Irritates skin and mucous linings of the eyes and respiratory tract. cough.

If breathing difficulties occur (e.g. severe continual coughing):

Keep patient half sitting with upper body raised.  
Keep warm and in a quiet place.  
Call a physician immediately.

**Skin contact**

After contact with skin, wash immediately with plenty of water.  
Consult a physician.  
Take off immediately all contaminated clothing.

**Eye contact**

With eye held open, thoroughly rinse immediately with plenty of water for at least 10 minutes.  
Protect unharmed eye.  
Continue rinsing process with eye rinsing solution.

Call ambulance. (Cue: caustic burn of the eyes)

Immediate further treatment in ophthalmic hospital/ ophthalmologist.  
Continue rinsing eye until arrival at ophthalmic hospital.

**Ingestion**

Do not induce vomiting.  
Danger of penetration of the lungs (danger to breathing) when swallowed or vomited, due to gas evolution and foam formation.

Only when patient fully conscious:

Have the mouth rinsed with water.  
Have patient drink plenty of water in small sips.  
Keep patient warm and at rest.

Notify ambulance immediately (keyword: acid burn).

**Notes to physician**

Therapy as for chemical burn.  
Following inhalation:  
Formation of a toxic lung edema is possible if product continues to be inhaled despite acute irritative effect (e.g. if it is not possible to leave the danger area).  
Prophylaxis of a toxic lung oedema with inhalative steroids (Dexamethasone aerosol dosing spray, f.ex. auxilosone).  
If substance has been swallowed:  
Aspiration hazard!  
Risk of gaseous embolisms!  
In case of excessive strain on the stomach due to gas evolution, insert siphon tube.  
Early endoscopy in order to assess mucosa lesions in the oesophagus and stomach which may appear.  
If necessary, suck away leftover substance.  
Do not administer activated charcoal, since risk of release of large amounts of gas from hydrogen peroxide !

---

**5. FIRE-FIGHTING MEASURES**

Flash point	Not measurable (formation of foam) Method: ISO 2719
Lower explosion limit	no data available
Upper explosion limit	no data available
Autoignition temperature	395° C Method: DIN 51 794

**Suitable extinguishing media**

water spray foam dry powder carbon dioxide (CO2)

**Extinguishing media which must not be used for safety reasons**

organic compounds

**Specific hazards during fire fighting**

Contact with the following substances may cause inflammation: flammable substances.

Involved in fire, it may decompose yielding oxygen. Risk of overpressure and burst due to decomposition in confined spaces and pipes.

Release of oxygen may support combustion.

In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely. Keep away from heat. If necessary: In the case of fire, cool the containers that are at risk with water or dilute with water (flooding).

**Special protective equipment for fire-fighters**

In the case of fire, wear respiratory protective equipment independent of surrounding air and chemical protective suit.

**Further information**

Evacuate personnel to safe areas. Keep out unprotected persons. Keep unauthorised persons away.

Water used to extinguish fire should not enter drainage systems, soil, or stretches of water. Ensure there are sufficient retaining facilities for water used to extinguish fire. Contaminated fire-extinguishing water must be disposed of in accordance with the regulations issued by the appropriate local authorities. Fire residues should be disposed of in accordance with the regulations.

---

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions**

Product causes chemical burns.

Wear personal protective equipment; see section 8.

Evacuate personnel to safe areas.

Keep out unprotected persons.

Keep unauthorised persons away.

**Environmental precautions**

Observe regulations on prevention of water pollution (collect, dam up, cover up).

Do not allow to run into water channels, surface water, or into the ground.

**Methods for cleaning up**

Keep away from incompatible substances.

Keep away from flammable substances.

see section 10.

Clean contaminated surface thoroughly.

Recommended cleaning agent: water.

Dispose of absorbed material in accordance with the regulations.

see section 13.

With small amounts:

Dilute product with lots of water and rinse away.

see section 12.

or

Absorb with liquid-binding material, e. g.: chemisorption, diatomaceous earth, universal binder

Do not use: textiles, saw dust, combustible substances.

Pick up mechanically. Collect in suitable containers.

**Additional advice**

Make safe or remove all sources of ignition.

Isolate defective containers immediately, if possible and safe to do.

Shut off leak, if possible and safe to do.

Place defective containers in waste receptacle (waste packaging receptacle) made of plastic (not metal).

Do not seal defective containers or waste receptacles airtight (danger of bursting due to product decomposition).

Never return spilled product into its original container for re-use. (Risk of decomposition.).

---

**7. HANDLING AND STORAGE****Handling****Safe handling advice**

Avoid contact with skin, eyes and clothing.

Do not breathe in vapours, aerosols, sprays.

For personal protection see section 8.

Handle in accordance with good industrial hygiene and safety practices.

Avoid impurities and heat effect.

Ensure there is good room ventilation.

Immediately change moistened and saturated work clothes.

Immediately rinse contaminated or saturated clothing with water.  
Never return spilled product into its original container for re-use. (Risk of decomposition.)

Provide for installation of emergency shower and eye bath.  
Set up safety and operation procedures.

#### Advice on protection against fire and explosion

Avoid sun rays, heat, heat effect.  
Keep away from sources of ignition - No smoking.

Keep away from flammable substances.  
Keep away from incompatible substances.  
see section 10.

To cool, spray closed containers with water spray jet. In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely.  
see section 5.

### Storage

#### Requirements for storage areas and containers

cool, well ventilated, clean, lockable.  
Recommendation: Acid-proof floor.  
Use adequate venting devices on all packages, containers and tanks and check correct operation periodically.  
Do not confine product in unvented vessels or between closed valves.  
Risk of overpressure and burst due to decomposition in confined spaces and pipes.  
Check containers and tanks at regular intervals to detect any special changes such as pressure build-up (distension), damage, leakage.  
Transport and store container in upright position only.  
Do not empty container by means of pressure.  
Always close container tightly after removal of product.  
Do not keep the container sealed.  
Ensure tightness at all times. Avoid leakage.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Only use containers which are specially permitted for: Peracetic acid.  
and/or  
For transport, storage and tank installations only use suitable materials.  
Suitable materials stainless steel (1.4571)  
Suitable materials polyethylene, polypropylene, polyvinyl chloride (PVC),  
Suitable materials polytetrafluoroethylene, glass, ceramics.  
Unsuitable materials mild steel, Iron, copper, brass, Bronze, aluminium, zinc.

#### Further information

Avoid sun rays, heat, heat effect.  
Avoid impurities.  
see also section 15.

Regularly verify the availability of water to deal with emergencies (for cooling, tank flooding, fire fighting) and check correct operation periodically.

For detailed information on design specifications for the construction of tank- and dosing installations ask the producer for advice.

#### Advice on common storage

Do not store together with: alkalis, reductants, metallic salts (risk of decomposition).

Do not store together with: inflammable substances (risk of fire).

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational exposure controls

#### • Hydrogen peroxide

CAS-No.	7722-84-1	
Control parameters	1 ppm	Time Weighted Average (TWA):(ACGIH)
	1 ppm	Recommended exposure limit (REL):(NIOSH)
	1.4 mg/m3	
	1 ppm	PEL:(OSHA Z1)
	1.4 mg/m3	
	1 ppm	Time Weighted Average (TWA):(OSHA Z1A)
	1.4 mg/m3	
	1 ppm	Time Weighted Average (TWA) Permissible Exposure
	1.4 mg/m3	Limit (PEL):(US CA OEL)
		(ACGIH)
Listed.		(US CA OEL)

Listed.

- **Acetic acid**

CAS-No.

64-19-7  
10 ppm  
15 ppm  
10 ppm  
25 mg/m<sup>3</sup>  
10 ppm  
25 mg/m<sup>3</sup>  
40 ppm  
15 ppm  
37 mg/m<sup>3</sup>

Time Weighted Average (TWA):(ACGIH)  
Short Term Exposure Limit (STEL):(ACGIH)  
PEL:(OSHA Z1)

Time Weighted Average (TWA) Permissible Exposure  
Limit (PEL):(US CA OEL)  
Ceiling Limit Value:(US CA OEL)  
Short Term Exposure Limit (STEL):(US CA OEL)

**Other information**

Suitable measuring processes are:

hydrogen peroxide

OSHA method ID 006

OSHA method VI-6

Acetic acid

NIOSH method 1603

OSHA method ID 186

**Engineering measures**

Ensure suitable suction/aeration at the work place and with operational machinery.  
see also section 7.

**Personal protective equipment**

**Respiratory protection**

Do not inhale vapour, aerosols, mist.

In case of larger quantities: If open handling is unavoidable:

If workplace exposure limit is exceeded apply Respiratory protective equipment.

wear a self contained respiratory apparatus

Respirator with A2B2E2K1P2 combination filter (Draeger)

Respirator with OV/AG combination filter (3M)

Respirator with ABEK2P3 combination filter (3M)

If necessary: Local ventilation.

**Hand protection**

Polychloroprene (PCP)

**Eye protection**

wear basket-shaped glasses or safety glasses with side shields when handling larger quantities; protective screen.

**Skin and body protection**

Wear protective clothing, acid-proof.

Suitable materials are:

PVC, neoprene, nitrile rubber (NBR), rubber.

Rubber or plastic boots.

**Hygiene measures**

Avoid contact with skin, eyes and clothing.

Do not inhale vapour, aerosols, mist.

Ensure there is good room ventilation.

Avoid contaminating clothes with product.

Immediately change moistened and saturated work clothes.

Immediately rinse contaminated or saturated clothing with water.

Any contaminated protective equipment is to be cleaned after use.

No eating, drinking, smoking, or snuffing tobacco at work.

Wash face and/or hands before break and end of work.

Preventive skin protection recommended.

Use barrier cream regularly.

**Protective measures**

Handle in accordance with good industrial hygiene and safety practices.

The work-place related airborne concentrations have to be kept below of the indicated exposure limits.

If the limits at the workplace are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Form	Liquid
Color	colourless, clear
Odor	Stinging

### Safety data

pH	ca. 0.6 (20 °C) Medium: Product
Melting point/range	ca. -28 °C
Boiling point/range	not applicable decomposition > 60 °C
Flash point	Method: ISO 2719 Not measurable (formation of foam)
Autoignition temperature:	395 °C Method: DIN 51 794
Autoinflammability	not spontaneously flammable
Lower explosion limit	no data available
Upper explosion limit	no data available
Vapour pressure	ca. 27 hPa (20 °C)
Density	ca. 1.12 g/cm <sup>3</sup> (20 °C)
Bulk density	not applicable
Water solubility	completely miscible
Partition coefficient (n-octanol/water)	log Pow: -1.25 measured as peracetic acid
Viscosity, dynamic	not determined

### Further information

Miscibility in water	completely miscible
Other information	oxidising agent oxidizing (according to EC Directive 67/548/EEC)

---

## 10. STABILITY AND REACTIVITY

Conditions to avoid	sun rays, heat, heat effect
Materials to avoid	Impurities, decomposition catalysts, metal salts, alkalis, reducing substances., metals, nonferrous heavy metal, aluminium, zinc., Possible hazardous reaction: decomposition.  flammable materials, Possible hazardous reaction: Spontaneous ignition.  organic solvents, Possible hazardous reaction: Danger of explosion.
Hazardous decomposition products	decomposition products Under conditions of thermal decomposition: steam, oxygen
Hazardous reactions	Product is a(n) oxidizing agent and reactive. Stable under recommended storage conditions. Product is supplied in stabilised form.

Danger of decomposition if exposed to heat

When coming in contact with the product, impurities, decomposition catalysts, metallic salts, alkalis, reducing agents may lead to self-accelerated, exothermic decomposition and the formation of oxygen.

Risk of overpressure and burst due to decomposition in confined spaces and pipes.  
Release of oxygen may support combustion.

---

## 11. TOXICOLOGICAL INFORMATION

Product Acute oral toxicity	LD50 Rat: 1859 mg/kg Method: Literature Test substance: Peracetic acid 5 %
Component Acute inhalation toxicity	LC50 rat: 0.49 mg/l Vapor as peracetic acid
Product Acute dermal toxicity	LD50 rat: 1147 mg/kg Method: literature Test Substance: Peracetic acid 5%
Product Skin irritation	Rabbit / 0.75 h corrosive Method: OECD test guideline 404 Test substance: Peracetic acid 5%
Product Eye irritation	Rabbit corrosive Method: literature Test substance: Peracetic acid 5 %
Product Sensitization	Draize-test guinea pig: negative Method: literature Test substance: Peracetic acid 5 %
Product Genotoxicity in vitro	Amestest predominantly negative Method: literature  Unscheduled DNA synthesis-test (UDS) Negative (literature value)  Chromosomal aberration V79 cells Negative Method: OECD TG 473  HGPRT-Test V 79 cells Negative Method: OECD TG 476
Product Genotoxicity in vivo	Micronucleus test Mouse, oral negative Method: Literature  Unscheduled DNA synthesis -test (UDS) Rat negative Method: literature
Product Human experience	Caustic, Irritation and on occasion caustic effects to the skin and mucous membranes (eyes, respiratory channels, in the stomach/intestinal tracts after swallowing) are to be expected from local contact. Also in diluted solutions onset of effects within seconds or minutes depending on concentration.

## 12. ECOLOGICAL INFORMATION

### Elimination information (persistence and degradability)

Biodegradability	Readily biodegradable. Exposure time: 28 d
------------------	---

	Method: OECD TG 301 E At non-bacteriotoxic concentrations
Physico-chemical removability	Method: literature Hydrolyses after 7 days by approx. 50 %. pH 4, Hydrolyses after 1 day to approx. 50% pH 7 and pH 9
Further Information	Under ambient conditions quick hydrolysis, Reduction or decomposition occurs. The following substances are formed: oxygen, water, acetic acid. Acetic acid is easily biodegradable

#### Behaviour in environmental compartments

Bioaccumulation	Low log Pow: see chapter 9
-----------------	-------------------------------

#### Ecotoxicity effects

Toxicity to fish	LC50 Pleuronectes platessa: 11 mg/l / 96 h Method: literature As peracetic acid  LC50 Oncorhynchus mykiss: 1-2 mg/l / 96 h Method: literature As peracetic acid
Toxicity to daphnia	EC50 Daphnia magna: .5 – 1.1 mg/l / 48 h Method: OECD TG 202 As peracetic acid (literature value)
Toxicity to algae	IC 50 selenastrum capricornutum: ca. 0.18 mg/l / 120 h Method: US-EPA-method Chronic As peracetic acid (literature value)
Toxicity to bacteria	EC50 Activated sludge: 5:1 mg/l / 3 h Method: OECD TG 209 As peracetic acid
Chronic toxicity in daphnia	NOEC Daphnia magna: 0.05 mg/l / 21 d Method: OECD 211 As peracetic acid

#### Further information on ecology

AOX	The product does not contain any organically bonded halogen.
General Ecological Information	does not contain any heavy metals and compounds from EC directive 76/464:  e.g. arsenic-, lead cadmium Mercury organic compounds organic halogen compounds

---

### 13. DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL

Advice on disposal	Disposal according to local authority regulations. Recommendation: Offer surplus and non-recyclable solutions to a licensed disposal company. Taking into account local regulations the product may be disposed of as waste water after neutralisation. If necessary contact the relevant authorities.
--------------------	--

---

### 14. TRANSPORT INFORMATION

**D.O.T. Road/Rail**

Class	5.1
UN-No	3149
Packing group	II
Subsidiary risk	8
Proper shipping name	Hydrogen peroxide and peroxyacetic acid mixtures, stabilized

**Sea transport IMDG-Code**

Class	5.1
UN-No	3149
Packaging group	II
Subsidiary risk	8
EmS	F-H, S-Q
Proper technical name (Proper shipping name)	HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED

**Air transport ICAO-TI/IATA-DGR**

Class	5.1
UN-No	3149
Packaging group	II
Subsidiary risk	8
Proper technical name (Proper shipping name)	Hydrogen peroxide and peroxyacetic acid mixture stabilized

**Loading instructions/Remarks**

IATA_C	ERG-Code 5C
IATA_P	ERG-Code 5C
IMDG	On deck only H: see chapter 3.2, Column 17IMDG code
IMDG	"Separated from" permanganates and class 4.1.

**Transport/further information**

Protect from thermal radiation.

---

**15. REGULATORY INFORMATION****Information on ingredients / Non-hazardous components**

This product contains the following non-hazardous components

Water				
CAS-No.	7732-18-5	Percent (Wt./ Wt.)	61 %	

**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

**Clean Air Act Section (112)**

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- None listed

**CERCLA Reportable Quantities**

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- Acetic acid  
CAS-No. 64-19-7  
Reportable Quantity 73529 lbs

**SARA Title III Section 311/312 Hazard Categories**

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard

**SARA Title III Section 313 Reportable Substances**

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- None listed

**Toxic Substances Control Act (TSCA)**

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

**Other US Federal Regulatory Information**

Other countries: observe the national regulations.

**State Regulations****California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

- None listed

**International Chemical Inventory Status**

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact JET Harvest Solutions Corporation Product Regulatory Department:

- USA (TSCA) Listed/registered

---

**16. OTHER INFORMATION****HMIS Ratings**

Health :	3
Flammability :	1
Physical Hazard :	1

**Further information**

Data for the production of the safety data sheet from the studies available and from the literature.

Further information about the characteristics of the product can be found in the product code of practice or in the Product-Brochure .

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The logo for JET-AG features a stylized 'E' symbol on the left, composed of three horizontal bars of varying lengths. To the right of this symbol, the text 'JET-AG' is written in a bold, italicized, red sans-serif font.